

**Supplement to Asteroids Deluxe™
Operation, Maintenance and Service Manual
(TM-165, 2nd printing)**

Instructions for Game Option Settings

Extensive field testing and recent marketing surveys indicate that our suggested setting of 2 ships per game needs to be changed. Therefore, Asteroids Deluxe™ is shipped with 3 ships per game.

Mark the Figure 7 in your Asteroids Deluxe Operation, Maintenance and Service Manual, 2nd printing, with the correction below. It shows Atari's current recommended setting.

Figure 7 Game Option Settings

To change toggle positions on the switch assemblies, you need not remove the game PCB. The switches, usually colored blue, are easily accessible when the Asteroids Deluxe™ Game PCB is mounted in place.

When changing the options, verify proper results on the monitor display by **performing the self-test**. Note that changing an option on any of the following eight toggles will cause an immediate change on the monitor screen during the self-test.

| Toggle Settings of 8-Toggle Switch on Asteroids Deluxe PCB (at R5—LEFT switch when PCB is in game) | | | | | | | | Option |
|---|-----|----------|-----|-----|-----|-----|-----|--------------------------------------|
| 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | |
| | | | | | | On | On | English language \$ |
| | | | | | | On | Off | German language |
| | | | | | | Off | On | French language |
| | | | | | | Off | Off | Spanish language |
| | | | | On | On | | | Game starts with 2 ships |
| | | | | On | Off | | | Game starts with 3 ships \$ |
| | | | | Off | On | | | Game starts with 4 ships |
| | | | | Off | Off | | | Game starts with 5 ships |
| | | Not Used | | | | | | 1-play minimum \$ |
| | | | On | | | | | 2-play minimum |
| | | | Off | | | | | Bonus ship at every 10,000 points \$ |
| On | On | | | | | | | Bonus ship at every 12,000 points |
| On | Off | | | | | | | Bonus ship at every 15,000 points |
| Off | On | | | | | | | No bonus ship |
| Off | Off | | | | | | | |

CHANGE
If set for no bonus ship or 50¢ play, add 1 ship per setting.

\$ Manufacturer's suggested settings

